

according to 1907/2006/EC, Article 31

Preparation date: 27.10.2021

Revision: 27.10.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier
• Trade name: FAWORI ACRYLIC SPRAY PAINT RAL 4008 PURPLE • 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
· Application of the substance / the mixture Acrylic spray paint
<ul> <li>1.3 Details of the supplier of the safety data sheet</li> <li>Manufacturer/Supplier: COLORPACK s.r.l. Via B.Cellini 26, 20020 Solaro, Milano - Italia Faks +39 029691714 Tel.+39 029690664 (8.30-17.00 Pazartesi 'den Cuma'ya) Web sitesi: www.colorpack.com e-mail: info@colorpack.com</li> <li>Further information obtainable from: R&amp;D Department</li> <li>1.4 Emergency telephone number: 0090 262 678 30 00 COLORPACK s.r.l. Tel.+39 029690664 (8.30-17.00 Pazartesi 'den Cuma'ya) Medikal: Centro Antiveleni di Milano - Azienda Ospedaliera Niguarda Cà Granda - Tel. 02/66101029 Ulusal Zehir Danışma Merkezi (UZEM) : 114</li> </ul>
SECTION 2: Hazards identification
SECTION 2. Huganas menujicanon

2.1 Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2H319Causes serious eye irritation.STOT SE 3H336May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

*The product is classified and labelled according to the CLP regulation.* • *Hazard pictograms* 



· Signal word Danger

• *Hazard-determining components of labelling:* acetone *n-butyl acetate* 

(Contd. on page 2)

according to 1907/2006/EC, Article 31

### Preparation date: 27.10.2021

Revision: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 1)

Hazard statements	
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated	
H319 Causes serious eye irritation.	
H336 May cause drowsiness or dizziness.	
Precautionary statements	
<i>P101</i> If medical advice is needed, have product container or label at have	nd.
P102 Keep out of reach of children.	
P103 Read label before use.	
P210 Keep away from heat, hot surfaces, sparks, open flames and	other ignition sources. No
smoking.	C
P251 Do not pierce or burn, even after use.	
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.	Remove contact lenses, if
present and easy to do. Continue rinsing.	
P405 Store locked up.	
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50	) °C/122 °F.
<i>P501</i> Dispose of contents/container in accordance with local/region	
regulations.	
2.3 Other hazards	
Results of PBT and vPvB assessment	

· **PBT:** Not applicable. · vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

#### · 3.2 Chemical characterisation: Mixtures

· Description:

• Dangerous compone	nts:	
	cosolvent	<i>≤</i> 2.5%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	
CAS: 67-64-1	acetone	25-50%
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 68476-40-4	Hydrocarbons, C3-4	25-50%
EINECS: 270-681-9	🚸 Flam. Gas 1, H220; Press. Gas (Comp.), H280	
CAS: 1330-20-7	xylene	10-25%
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 123-86-4	n-butyl acetate	2.5-10%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 110-82-7	cyclohexane	<i>≤ 2.5%</i>
EINECS: 203-806-2	� Flam. Liq. 2, H225; � Asp. Tox. 1, H304; ∳ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ∲ Skin Irrit. 2, H315; STOT SE 3, H336	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

according to 1907/2006/EC, Article 31

Preparation date: 27.10.2021

Trade name: FAWORI ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 2)

- *After swallowing: If symptoms persist consult doctor.*
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
  - No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6:** Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

*Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.* 

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

GB

Preparation date: 27.10.2021

Revision: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 3)

Ingredients with limit values that require monitoring at the workplace:	(Contd. of page 2
67-64-1 acetone	
WEL Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm	
Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm	
1330-20-7 xylene	
WEL Short-term value: 441 mg/m <sup>3</sup> , 100 ppm	
Long-term value: 220 mg/m <sup>3</sup> , 50 ppm	
Sk, BMGV	
123-86-4 n-butyl acetate	
WEL Short-term value: 966 mg/m <sup>3</sup> , 200 ppm	
Long-term value: 724 mg/m <sup>3</sup> , 150 ppm	
111-76-2 2-Butoxyethanol	
WEL Short-term value: 246 mg/m <sup>3</sup> , 50 ppm	
Long-term value: 123 mg/m <sup>3</sup> , 25 ppm	
Sk, BMGV	
Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV 650 mmol/mol creatinine	
Medium: urine	
Sampling time: post shift	
Parameter: methyl hippuric acid	
111-76-2 2-Butoxyethanol	
BMGV 240 mmol/mol creatinine	
Medium: urine	
Sampling time: post shift	
Parameter: butoxyacetic acid	
Additional information: The lists valid during the making were used as basis.	
8.2 Exposure controls	
Personal protective equipment:	
General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes.	
Avoid contact with the eyes and skin.	
Respiratory protection:	
In case of brief exposure or low pollution use respiratory filter device. In case of in	tensive or longer exposure u
self-contained respiratory protective device.	
Protection of hands:	
Protective gloves	
Trolective gioves	
The glove material has to be impermeable and resistant to the product/ the substance	ce/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 5)

GB

#### Preparation date: 27.10.2021

Revision: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 4)

• Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

## The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• *Eye protection:* Safety glasses

Tightly sealed goggles

### **SECTION 9: Physical and chemical properties**

· 9.1 Information on basic physical and chemical properties	
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
• Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	: Not applicable, as aerosol.
· Flash point:	$< \theta \circ C$
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	>400 °C
Decomposition temperature:	Not determined.
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	9.5 Vol %
· Vapour pressure at 20 °C:	4.5 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density at 20 °C	>1 (hava=1) g/cm <sup>3</sup>
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with	
water:	Partly miscible.
• Partition coefficient: n-octanol/water:	Not determined.
	(Contd. on page 6)

according to 1907/2006/EC, Article 31

Preparation date: 27.10.2021

Revision: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
VOC (EC)	84 %	
· 9.2 Other information	No further relevant information available.	

### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

• 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

### 110-82-7 cyclohexane

Oral LD50 12,705 mg/kg (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation
- Causes serious eye irritation.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- *Reproductive toxicity Based on available data, the classification criteria are not met.*

• STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

according to 1907/2006/EC, Article 31

Preparation date: 27.10.2021

Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 6)

Revision: 27.10.2021

#### • Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. • 12.5 Results of PBT and vPvB assessment

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

• 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport informat	ion
· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name	
·ADR	1950 AEROSOLS
· IMDG	AEROSOLS
·IATA	AEROSOLS, flammable
· 14.3 Transport hazard class(es)	
· ADR	
· Class	2 5F Gases.
· Label	2.1
· IMDG, IATA	
· Class	2.1
·Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	-
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
· 14.6 Special precautions for user	Warning: Gases.
	(Contd. on pag

Preparation date: 27.10.2021

Revision: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

	(Contd. of page 7
Hazard identification number (Kemler code):	-
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre
	Category A. For AEROSOLS with a capacity above 1 litre
	Category B. For WASTE AEROSOLS: Category C, Clear of
	living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre:
	Segregation as for class 9. Stow "separated from" class except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · National regulations:
- · Information about limitation of use:
  - Class Share in %

NK 55.5

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

H220 Extremely flammable gas. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour.

(Contd. on page 9)

GB

Preparation date: 27.10.2021

### Trade name: FAWORİ ACRYLIC SPRAY PAINT RAL 4008 PURPLE

(Contd. of page 8) H280 Contains gas under pressure; may explode if heated. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. · Contact: Gülay Coşkun Sezer / TSE - MSDS preparer certified. Certificate no and document date: GBF-A-0-3118 / 27.06.2020 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard - Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 GB