

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: FAWORI PANEL DOOR PAINT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against FURNITURE COATINGS
- · Application of the substance / the mixture FURNITURE COATINGS
- 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S. G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68 busemuzeyyen.poyraz@betek.com.tr • Further information obtainable from: R&D Department

· 1.4 Emergency telephone number: 00902626783000

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Repr. 2	H361d	Suspected of damaging the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

(Contd. of page 1)

• Hazard-determ	ining components of labelling:
toluene	
· Hazard statem	ents
H225 Highly	flammable liquid and vapour.
H315 Causes	skin irritation.
H361d Suspect	ed of damaging the unborn child.
H336 May ca	use drowsiness or dizziness.
H373 May ca	use damage to organs through prolonged or repeated exposure.
H304 May be	fatal if swallowed and enters airways.
· Precautionary	statements
P101	If medical advice is needed, have product container or label at hand.
P102	Keep out of reach of children.
P103	Read label before use.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P303+P361+P	353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	[or shower].
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· 2.3 Other haza	rds
· Results of PBT	and vPvB assessment
DDT. Not ann!	icable

• *PBT:* Not applicable.

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	ents:	
CAS: 108-88-3	toluene	10-25%
EINECS: 203-625-9		
CAS: 123-86-4	n-butyl acetate	2.5-10%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
• Additional informat	ion: For the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3) GB

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

(Contd. of page 2)

• **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

SECTION 5: Firefighting measures

- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

• Requirements to be met by storerooms and receptacles: Keep in cool, dry, ventilated storage and closed container. keep away from heat, direct sun light and open flame. keep between +5 - +30 C.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

^{· 5.1} Extinguishing media

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

 $(Contd. \ of \ page \ 3)$

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

• Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

· Additional information: The lists valid during the making were used as basis.

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

(Contd. on page 5)

GF

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

9.1 Information on basic physical and ch General Information Appearance:	emical properties
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Undetermined.
Flash point:	< 23 °C
Ignition temperature:	535 °C
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapou mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.0 Vol %
Vapour pressure at 20 °C:	29 hPa
Density at 20 °C:	1.5 g/cm ³
Solubility in / Miscibility with	
water:	Fully miscible.
Solvent content:	
Organic solvents:	24.6 %
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 value	s relevant j	for classification:
-----------------	--------------	---------------------

108-88-3 toluene

Oral LD50 5000 mg/kg (rat)

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

(Contd. of page 5)

DermalLD5012124 mg/kg (rabbit)InhalativeLC50/4 h5320 mg/l (mouse)

· Primary irritant effect:

· Skin corrosion/irritation

Causes skin irritation.

- Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity
- Suspected of damaging the unborn child.
- · STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard
- May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.

(Contd. on page 7)

GF

Safety data sheet according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

(Contd. of page 6)

14.1 UN-Number ADR, IMDG, IATA	1263	
14.2 UN proper shipping name ADR IMDG, IATA	1263 PAINT or PAINT RELATED MATERIAL (TOLUENE) PAINT or PAINT RELATED MATERIAL (TOLUENE)	
14.3 Transport hazard class(es)		
ADR		
Class Label	3 (F1) Flammable liquids.	
IMDG, IATA		
Class Label	3 Flammable liquids. 3	
14.4 Packing group ADR, IMDG, IATA	Ш	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number:	Warning: Flammable liquids. 33 F-E, <u>S-E</u>	
14.7 Transport in bulk according to Annex II o Marpol and the IBC Code		
Transport/Additional information:		
ADR Limited quantities (LQ) Transport category Tunnel restriction code	LQ4 2 D/E	
UN "Model Regulation":	UN1263, PAINT, 3, II	

(Contd. on page 8)

according to 1907/2006/EC, Article 31

Preparation date: 01.09.2021

Revision: 28.10.2013

Trade name: FAWORI PANEL DOOR PAINT

(Contd. of page 7)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

· Information about limitation of use:

ClassShare in %I0.2

NK 24.6

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

GB