



GLUE PRODUCT GROUP

Fawori PVA White Adhesive

PRODUCT DESCRIPTION

Fawori White Wood Glue is a water-based, polyvinyl-acetate based glue that can be used in coating, gluing and solid coating all types of wood with its high adhesive power.

SPECIFICATIONS

Creates a flexible and firm layer that resembles frosted glass after drying.

Solid substance %: 52-56

Viscosity: 10000-15000 (20 ° C)

Ph (20°C) : 6-8

APPLICATION

It can be used in hot and cold presses. 5-15 minutes of pressing with a pressure of 2-5 kg/cm² is enough for good adhesion. The time period may vary depending on the type of wood and press temperature. Remove dust, grease, resin residue and all types of stain from the application surface. Apply the glue using a brush, roller or automatic tools. Glue within maximum 10 minutes following the application. Ensure that the surface and ambient temperatures are between +5 to +30 °C for good adhesion. Close the lid of the package firmly after the application. Clean the application tools using water. Do not use rusty tools in the application process.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568. For MSDS and TDS forms providing information about application details, health-safety-handling risks and precautions, visit www.fawori.com.tr.

DRYING TIME (at 20°C, 65% RH)

Varies between 0.5 to 2 hours depending on the thickness of the applied film, the type of the application surface, the temperature and the humidity of the environment.

CONSUMPTION

Depending on the film thickness and the surface, 1kg of glue can be applied to an area of 4-6m². Performing a controlled sample run to estimate the precise consumption is recommended.

STORAGE

It can be stored for 1 year in its unopened original package, in a cool and dry place at 0-40 ° C, away from frost and direct sunlight.

PACKAGE

25 Kg, 20 Kg, 10 Kg, 3 Kg, 0,85 Kg

Warning Statement

Caution HAZARD

STATEMENT

H317 May cause allergic skin reactions.

PRECAUTIONARY STATEMENTS

P101 If medical advice is needed, keep the product container or label.

P102 Keep out of the reach of children.

P103 Read label before use.

P261 Avoid breathing its dust/fume/gas/mist/vapor/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P321 Specific treatment required (see label).

P363 Wash contaminated clothing before reuse.



P333+P313 If skin irritation or itching occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

Hazard-determining components for labeling:

Mixture: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1); mixture: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] urea tetramethylol astylene

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

Where necessary, please refer to Material Safety Data Sheets for more information on health, safety and handling risks, and precautions associated with the products.

This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.

Rev2 April 2020