



# Fawori Wood Stain Varnish

## PRODUCT DESCRIPTION

Alkyd-binder-based, transparent, glossy, decorative and protective top-coat wood varnish that is designed for wood surfaces.

## SPECIFICATIONS

Protective against fungi on surfaces thanks to its special additives. Protects the wood against water and ultraviolet rays. Easily penetrates the wood. Resistant against corrosion. Creates a coating layer on the surface.

## APPLICATION SURFACES

Used for painting of all types of wood cladding and wood garden furniture. Avoid using on hives, saunas, wood containing unpackaged food materials, horizontal wood floors and wood surfaces exposed to foot traffic. Avoid applying on wooden surfaces containing high concentrations of natural oil like teak and iroko.

## APPLICATION

Fawori Wood Stain Decorative Wood Varnish is recommended to be stirred before application. Apply in two coats using a brush, roller or spray gun and wait 8 hours between coats. Clean the application surfaces from grease, dirt, resin and dust, and then sand and remove the dust if required. Burn the knots if any and wipe out the resins with Fawori Cellulosic Thinner. Apply 1 or 2 coats before application to support the protection of raw wood against fungi, mold and wood worms. Fawori Wood Stain Decorative Wood Varnish can be applied after 24 hours. Sand slightly, wipe with a clean cloth and paint with the same color on the surface when it is required to reapply Fawori Wood Stain Decorative Wood Varnish to surfaces that are previously treated with the same product. Remove blistering and flaking areas and then begin the application. Recommended to be applied in two coats. Note that the color gets darker as the number of coats increases. Apply the same number of coats in ongoing work. Ensure the humidity of the application wood is not over 15%.

Note: It is recommended to color the top coat by 15% in average to increase the UV resistance in cases where a natural look is desired. Avoid applying products like linseed oil, synthetic paste and filler varnish to surfaces during substructure repairs. Ensure that there is a colored protective film on the sublayer for full UV resistance if a transparent protector is used on the top coat in exterior wood protecting system applications. Responsibility of avoiding this step fully belongs to the consumer. Ensure that the ambient and surface temperatures are between +5°C and +30°C during application and until the products are fully dried, and protect the surfaces against frost. Equipment used must be cleaned with Fawori Synthetic Thinner immediately after application.

Our products should be applied on substructure surfaces that are built in line with General Construction Specifications dated 30.06.2007 and with No. 26568. For MSDS and TDS forms providing information about application details, health-safety-handling risks and precautions, visit [www.fawori.com.tr](http://www.fawori.com.tr).

## Airless Spraying:

Pressure	: 120-140 bar
Nozzle Angle	: 50°
Nozzle Size (inch)	: 0.010"
Thinning	: Ready to use Never thin.

## THINNING

Ready to use Do not thin.

## DRYING TIME (at 20°C, 65% RH)

Touch dry: 1-2 hours

Hard-dry: 12 hours (drying time may increase at higher relative humidity and lower temperature)

**CONSUMPTION**

Can be applied on an area of 11-18 m<sup>2</sup> in a single coat with 1 Liter based on the type and absorbency of the wood. Color and consumption may vary depending on the wood type, surface state, number of coats and application method. Perform a controlled sample run to estimate the precise consumption amount.

**FLASH POINT**

36°C

**STORAGE**

It can be stored in a cool and dry environment in its unopened packaging protected against frost and direct sunlight. Close the lid air-tight immediately after application.

**PACKAGE**

12 Liter, 2,5 Liter, 0,75 Liter

**WARNING STATEMENT**

Hazard

**HAZARD STATEMENTS**

H226: Inflammable liquid and vapor.

H304 Fatal if inhaled or swallowed.

**PRECAUTIONARY STATEMENTS**

P101 If medical advice is needed, have the product container or label at hand.

P102 Keep out of reach of children.

P103 Read the label before use.

P210 Keep away from heat/sparks/flame/hot surfaces - No smoking.

P241: Use explosion proof electrical/ventilating/lighting/.../equipment.

P301+P310 IF SWALLOWED: CALL NATIONAL POISON CONSULTING CENTER AT 114/Call a doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse your skin with water/shower.

P405: Store locked up.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**Hazard-determining components for labeling:** solvent naphtha (petroleum), medium aliphatic

**Pose No.**

Y.25.001/05

**Rate No.**

04,561/02

This technical sheet is prepared based on laboratory data at normal conditions. Consult technical personnel for details that are not provided above. Otherwise, the manufacturing company cannot be held responsible for failures that may arise due to lack of knowledge. Our company reserves the right to change the information provided.

**This product is manufactured by Betek A.Ş., with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001, TS ISO 10002, TS ISO/IEC 27001.**

**Rev4 April 2019**