

Preparation date: 24.03.2020

Page 1/10

Revision: 24.03.2020

Safety data sheet

according to 1907/2006/EC, Article 31

1.1 Product identifie		
	İ SELÜLOZİK PARLAK VERNİK l uses of the substance or mixture and uses advised against formation available.	
Application of the su	stance / the mixture A fast-drying, flexible top-coat varnish.	
1.3 Details of the sup	lier of the safety data sheet	
Manufacturer/Suppl	r:	
Betek Boya ve Kimya	Sanayi A.S.	
G.O.S.B. Tembelova	lani 3200 Sokak No:3206	
41400 Gebze/ Kocael	' Türkiye	
Tel: 00 90 262 678 3	00	
Fax: 00 90 262 641 2	68	
murat.kucukkul@bet	.com.tr	
\cup	btainable from: R&D Department	
	one number: 0090 262 678 30 00	

SECTION 2: Hazards identification

• 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

GHS08 health hazard

· · ·		
Repr. 1B	H360FD	May damage fertility. May damage the unborn child.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.
Asp. Tox. 1	H304	May be fatal if swallowed and enters airways.

 \land

GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK (Contd. of page 1) · Hazard pictograms GHS05 GHS07 GHS02 GHS(· Signal word Danger · Hazard-determining components of labelling: toluene butanol bis(2-ethylhexyl) phthalate ethylbenzene · Hazard statements H225 Highly flammable liquid and vapour. H315 Causes skin irritation. H318 Causes serious eye damage. H360FD May damage fertility. May damage the unborn child. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H304 May be fatal if swallowed and enters airways. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P103 Read label before use. IF SWALLOWED: Immediately call a POISON CENTER/ doctor. *P301+P310* P321 Specific treatment (see on this label). P331 Do NOT induce vomiting. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P362+P364 Take off contaminated clothing and wash it before reuse. P405 Store locked up. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: Contains α -[3-(1-oxoprop-2-eny)l-1-oxypropyl]dimethoxysilyloxy- ω -[3(1-oxoprop-2-enyl)-1-oxypropyl] dimethoxysilyl poly(dimethylsiloxane). May produce an allergic reaction. · 2.3 Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description:

· Dangerous components:

cosolvent	2.5-10%
Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	
H315; Eye Irrit. 2, H319	

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

CAS: 108-88-3	toluene	. of page 2 25-50%
EINECS: 203-625-9	� Flam. Liq. 2, H225; � Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; � Skin Irrit. 2, H315; STOT SE 3, H336	
	cellulose nitrate	10-25%
	🚸 Flam. Sol. 1, H228	
CAS: 67-64-1	acetone	10-25%
EINECS: 200-662-2	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 67-63-0	propan-2-ol	2.5-10%
EINECS: 200-661-7	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 123-86-4	n-butyl acetate	2.5-10%
EINECS: 204-658-1	🚸 Flam. Liq. 3, H226; 🚸 STOT SE 3, H336	
CAS: 78-83-1	butanol	2.5-10%
EINECS: 201-148-0	🚸 Flam. Liq. 3, H226; 🚸 Eye Dam. 1, H318; 🚸 Skin Irrit. 2, H315; STOT SE 3, H335-H336	
CAS: 117-81-7	bis(2-ethylhexyl) phthalate	2.5-10%
EINECS: 204-211-0	🚸 Repr. 1B, H360FD	
CAS: 193159-06-7	α -[3-(1-oxoprop-2-eny)l-1-oxypropyl]dimethoxysilyloxy- ω -[3(1-oxoprop-2-enyl)-	<i>≤ 2.5%</i>
ELINCS: 415-290-8	1-oxypropyl]dimethoxysilyl poly(dimethylsiloxane)	
	Skin Sens. 1, H317	
SVHC		

• Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- *After inhalation:* In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- *Protective equipment:* No special measures required.

(Contd. on page 4)

GB

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

 $(Contd. \ of \ page \ 3)$

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- *Keep container tightly sealed. Store in cool, dry conditions in well sealed receptacles.*
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

(Contd. on page 5)

GB –

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

(Contd. of page 4) 67-63-0 propan-2-ol WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm 123-86-4 n-butyl acetate WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm 111-76-2 2-Butoxyethanol WEL Short-term value: 246 mg/m³, 50 ppm Long-term value: 123 mg/m³, 25 ppm Sk. BMGV 78-83-1 butanol WEL Short-term value: 231 mg/m³, 75 ppm Long-term value: 154 mg/m³, 50 ppm 117-81-7 bis(2-ethylhexyl) phthalate WEL Short-term value: 10 mg/m³ Long-term value: 5 mg/m³ Ingredients with biological limit values: 111-76-2 2-Butoxyethanol BMGV 240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid · Additional information: The lists valid during the making were used as basis. · 8.2 Exposure controls · Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin. · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

(Contd. of page 5)

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

9.1 Information on basic physical	and chemical properties
General Information	
Appearance:	
Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic
Change in condition Initial boiling point and boiling	range: Undetermined.
Flash point:	Not applicable.
Flammability (solid, gas):	Not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Density:	Not determined.
Solubility in / Miscibility with	
water:	Not determined.
9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on toxicological effects

· Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

(Contd. of page 6)

		(Conta. of page
· LD/LC50	values rele	vant for classification:
108-88-3 t	oluene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)
117-81-7 [ois(2-ethyll	hexyl) phthalate
Oral	LD50	30600 mg/kg (rat)
Dermal	LD50	25000 mg/kg (rabbit)
Serious ey Causes ser Respirator CMR effe Germ cell Carcinoge Reproduct May dama STOT-sin May cause STOT-rep May cause Aspiration	sion/irrita n irritation e damage/ vious eye do y or skin s cts (carcino mutagenic nicity Base vive toxicity ge fertility gle exposu e drowsines eated expo damage to hazard	tion irritation gamage. ensitisation Based on available data, the classification criteria are not met. ogenity, mutagenicity and toxicity for reproduction) wity Based on available data, the classification criteria are not met. ed on available data, the classification criteria are not met. % May damage the unborn child. re s or dizziness.
• 12.1 Toxid • Aquatic to • 12.2 Persi • 12.3 Bioad • 12.4 Mobi	ity xicity: No stence and ccumulativ lity in soil l ecologica	cological information further relevant information available. degradability No further relevant information available. e potential No further relevant information available. No further relevant information available. l information:

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8) GB

Safety data sheet according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

(Contd. of page 7)

• Uncleaned packaging: • Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT RELATED MATERIAL, special provision 640D
IMDG, IATA	PAINT RELATED MATERIAL
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label IMDG, IATA	3
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
14.7 Transport in bulk according to Ann	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category	Maximum nei quantity per outer packaging. 500 mi 2
Tunnel restriction code	D/E

according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

	(Contd. of page 8)
·IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN1263, PAINT RELATED MATERIAL, special provision 640D, 3, II

SECTION 15: Regulatory information

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 30, 48, 51a

· National regulations:

Class	Share in %
NK	64.7

· Other regulations, limitations and prohibitive regulations

· Substances of very high concern (SVHC) according to REACH, Article 57

117-81-7 bis(2-ethylhexyl) phthalate

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.

H360FD May damage fertility. May damage the unborn child.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Preparation date: 24.03.2020

Revision: 24.03.2020

(Contd. of page 9)

GB

Trade name: FAWORİ SELÜLOZİK PARLAK VERNİK

CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Flam. Sol. 1: Flammable solids – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Skin Sens. 1: Skin sensitisation – Category 1 Repr. 1B: Reproductive toxicity - Category 1B Repr. 2: Reproductive toxicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1