

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Revision: 24.03.2020

#### **SECTION 1:** Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Synthetic Paint
- 1.3 Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Betek Boya ve Kimya Sanayi A.S. G.O.S.B. Tembelova Alani 3200 Sokak No:3206 41400 Gebze/ Kocaeli/ Türkiye Tel: 00 90 262 678 30 00 Fax: 00 90 262 641 21 68 busemuzeyyen.poyraz@betek.com.tr
- Further information obtainable from: R&D Department
- 1.4 Emergency telephone number: 0090 262 678 30 00

#### **SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

flame

Flam. Liq. 3 H226 Flammable liquid and vapour.

health hazard

STOT RE 1H372Causes damage to the central nervous system through prolonged or repeated exposure.Asp. Tox. 1H304May be fatal if swallowed and enters airways.

#### · 2.2 Label elements

- · Labelling according to Regulation (EC) No 1272/2008
- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



Signal word Danger
 Hazard statements
 H226 Flammable liquid and vapour.
 H372 Causes damage to the central nervous system through prolonged or repeated exposure.
 H304 May be fatal if swallowed and enters airways.
 Precautionary statements
 P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.

(Contd. on page 2)

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Revision: 24.03.2020

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

	(Contd. of page 1)
P103	Read label before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P303+P361+P35	3 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water
	[or shower].
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
· Additional inform	nation:
Contains 2-butan	one oxime. May produce an allergic reaction.
Warning! Hazard	ous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
· 2 3 Other hazard	

2.3 Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

· vPvB: Not applicable.

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Chemical characterisation: Mixtures

· Description:

· Dangerous compone	ents:	
CAS: 64742-88-7	Solvent naphtha (petroleum), medium aliph.	25-50%
EINECS: 265-191-7	♦ Flam. Liq. 3, H226; ♦ STOT RE 1, H372; Asp. Tox. 1, H304; ♦ Acute Tox. 4, H332	
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	≤ 2.5%
EINECS: 265-150-3	🚸 Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304	
CAS: 96-29-7	2-butanone oxime	≤ 2.5%
EINECS: 202-496-6	Carc. 2, H351;  Eye Dam. 1, H318;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Sens. 1, H317	
CAS: 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	≤ 2.5%
EINECS: 265-185-4	🚸 Muta. 1B, H340; Carc. 1B, H350; STOT RE 1, H372; Asp. Tox. 1, H304	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	≤ 2.5%
EINECS: 265-199-0	<ul> <li>Flam. Liq. 3, H226;</li> <li>Muta. 1B, H340; Carc. 1B, H350; Asp. Tox. 1, H304;</li> <li>Acute Tox. 4, H332</li> </ul>	
· Additional informat	ion: For the wording of the listed hazard phrases refer to section 16.	

#### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

• After eye contact: Rinse opened eye for several minutes under running water.

• After swallowing: If symptoms persist consult doctor.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

GB

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

(Contd. of page 2)

#### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

#### **SECTION 6: Accidental release measures**

• 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- Do not flush with water or aqueous cleansing agents
- 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
Information about fire - and explosion protection:

- Keep ignition sources away Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

- · 8.1 Control parameters
- Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists valid during the making were used as basis.

(Contd. on page 4)

### Safety data sheet according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

(Contd. of page 3)

- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately.
- · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

### **SECTION 9: Physical and chemical properties**

• General Information • Appearance:	
Form:	Liquid
Colour:	According to product specification
· Odour:	Characteristic
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	153 °C
· Flash point:	Undetermined
· Ignition temperature:	265 °C
• Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.6 Vol %
Upper:	6.5 Vol %
· Vapour pressure at 20 °C:	6.6 hPa

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Revision: 24.03.2020

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

(Contd. of page 4)

• Density at 20 °C:

1.36-1.40 g/cm<sup>3</sup>

• Solubility in / Miscibility with water:

Not determined.

• 9.2 Other information

No further relevant information available.

#### **SECTION 10: Stability and reactivity**

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

· 10.4 Conditions to avoid No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### **SECTION 11: Toxicological information**

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:					
64742-88-7 Solvent naphtha (petroleum), medium aliph.					
Oral	LD50	>6500 mg/kg (rat)			
Dermal	LD50	>3000 mg/kg (rab)			
Inhalative	LC50/4 h	>14 mg/l (rat)			
64742-48-9	64742-48-9 Naphtha (petroleum), hydrotreated heavy				
Oral	LD50	>5000 mg/kg (rat)			
Dermal	LD50	>3000 mg/kg (rab)			
96-29-7 2-butanone oxime					
Oral	LD50	3700 mg/kg (rat)			
Dermal	LD50	200-2000 mg/kg (rat)			
Inhalative	LC50/4 h	20 mg/l (rat)			
64742-95-6 Solvent naphtha (petroleum), light arom.					
Oral	LD50	>6800 mg/kg (rat)			
Dermal	LD50	>3400 mg/kg (rab)			
Inhalative	LC50/4 h	>10.2 mg/l (rat)			
· Primary ir	Primary irritant effect:				

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

• Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• *Reproductive toxicity Based on available data, the classification criteria are not met.* 

· STOT-single exposure Based on available data, the classification criteria are not met.

(Contd. on page 6)

GB

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Revision: 24.03.2020

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

 $(Contd. \ of page \ 5)$ 

• STOT-repeated exposure Causes damage to the central nervous system through prolonged or repeated exposure. • Association hazard

• *Aspiration hazard May be fatal if swallowed and enters airways.* 

# **SECTION 12: Ecological information**

· 12.1 Toxicity

- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

#### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- *Recommendation: Disposal must be made according to official regulations.*

14.1 UN-Number ADR, IMDG, IATA	UN1263	
14.2 UN proper shipping name		
ADR	1263 PAINT	
IMDG, IATA	PAINT	
14.3 Transport hazard class(es) ADR		
Class	3 (F1) Flammable liquids.	

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

Revision: 24.03.2020

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT (Contd. of page 6) · Label 3 · IMDG, IATA 3 Flammable liquids. · Class · Label 3 · 14.4 Packing group III · ADR, IMDG, IATA • 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 30 · EMS Number: *F*-*E*,*S*-*E* · Stowage Category A • 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: ·ADR · Limited quantities (LQ) 5L• Excepted quantities (EQ) Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml 3 · Transport category D/E• Tunnel restriction code · IMDG · Limited quantities (LQ) 5LCode: E1 • Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml · UN "Model Regulation": UN 1263 PAINT, 3, III

#### **SECTION 15: Regulatory information**

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· National regulations:

· Information about limitation of use:

Class	Share in %
Ι	0.5
NK	27.4

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 8)

GE

according to 1907/2006/EC, Article 31

Preparation date: 06.09.2021

#### Trade name: FAWORI CERAMIX SEMI GLOSS SYNTHETIC PAINT

(Contd. of page 7)

GB

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H312 Harmful in contact with skin. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H332 Harmful if inhaled. H340 May cause genetic defects. H350 May cause cancer. H351 Suspected of causing cancer. H372 Causes damage to organs through prolonged or repeated exposure. Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organisation ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO) ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Skin Sens. 1: Skin sensitisation – Category 1 Muta. 1B: Germ cell mutagenicity - Category 1B Carc. 1B: Carcinogenicity - Category 1B Carc. 2: Carcinogenicity - Category 2 STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1 Asp. Tox. 1: Aspiration hazard - Category 1