



# Fawori Cellulosic Filler Varnish

## DESCRIPTION

Cellulose-based filler varnish applied to smooth the surface for the top coat varnish.

## APPLICATION SURFACES

Can be used safely on all types of MDF, massive wood, timber cover, parquet and wooden surfaces.

## APPLICATION

Remove any dust, dirt or grease. Sand the surface with 220 grit sandpaper, if required. Apply after thinning with Fawori Cellulosic Thinner to the right viscosity value. Recommended to be applied in 2 or 3 coats. Wait for 20 minutes after each coat.

Airless Spraying

Pressure: 120-140 bar

Nozzle Angle: 50° Nozzle Size: 0,010 inch

Thinning: 15%

## DRYING TIME

Touch dry: 30 minutes (20°C)

Sand dry: 3-4 hours (20°C)

## THINNING

Thin with Cellulosic Thinner by 30% in case of a smooth wood surface and by 60% in case of a rough, cracked wood surface.

## CONSUMPTION

1L can cover 8-10m<sup>2</sup> in a single coat depending on the application surface and method (excluding losses). Perform a controlled sample run to estimate the precise consumption amount.

## FLASH POINT

<23 °C



BETEK BOYA VE KİMYA SAN. A.Ş.

Headquarters: Zümrütevler Mahallesi Ural Sokak No:38 34852 Maltepe- İSTANBUL

Phone: (0216) 571 11 00 Fax: +90 (216) 571 13 15 – Central Registration System Number: 0167001238900018 - [www.fawori.com](http://www.fawori.com)



## **STORAGE**

Store in a well-ventilated place, away from direct sunlight. Can be stored for 1 year from the date of production in its unopened, original package.

## **PACKAGE**

12kg, 3kg

## **HAZARD STATEMENTS**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed or enters airways.

## **PRECAUTIONARY STATEMENTS**

P101 If medical advice is needed, keep the product container or label.

P102 Keep out of the reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion proof electrical/ventilating/lighting/.../equipment.

P301+P310 IF SWALLOWED: Immediately call THE NATIONAL POISON CONSULTING CENTER AT 114/a doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse your skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional, national and international regulations.

**This product is manufactured by Betek A.Ş. with certificate of conformity to the standards TS EN ISO 9001, TS EN ISO 14001, TS 18001, TS EN ISO 50001 and TS ISO 10002.**