



Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: FAWORİ CHROME EFFECT SPRAY PAINT COPPER**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Betek Boya ve Kimya Sanayi A.S.
G.O.S.B. Tembelova Alani 3200 Sokak No:3206
41400 Gebze/ Kocaeli/ Türkiye
Tel: 00 90 262 678 30 00
Fax: 00 90 262 641 21 68
busemuzeyyen.poyraz@betek.com.tr
- **Further information obtainable from: R&D Department**
- **1.4 Emergency telephone number: 0090 262 678 30 00**

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: **FAWORI CHROME EFFECT SPRAY PAINT COPPER**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07 GHS08 GHS09

· **Signal word** Danger· **Hazard-determining components of labelling:**

cyclohexane

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H410 Very toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Chemical characterisation: Mixtures**· **Description:**· **Dangerous components:**

| | | |
|--------------------------------------|--|---------|
| CAS: 68476-40-4 EINECS: 270-681-9 | Hydrocarbons, C3-4 Flam. Gas 1, H220; Press. Gas (Comp.), H280 | 25-50% |
| CAS: 110-82-7 EINECS: 203-806-2 | cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336 | 25-50% |
| CAS: 1330-20-7 EINECS: 215-535-7 | xylene Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 2.5-10% |
| CAS: 7440-50-8 EINECS: 231-159-6 | copper substance with a Community workplace exposure limit | 2.5-10% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31



Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: FAWORÌ CHROME EFFECT SPRAY PAINT COPPER

(Contd. of page 2)

CAS: 123-86-4 n-butyl acetate

EINECS: 204-658-1  Flam. Liq. 3, H226;  STOT SE 3, H336

2.5-10%

 · **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: **FAWORI CHROME EFFECT SPRAY PAINT COPPER**

(Contd. of page 3)

- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
- **Additional information about design of technical facilities:** No further data; see item 7.

· **Ingredients with limit values that require monitoring at the workplace:**

110-82-7 cyclohexane

| | |
|-----|--|
| WEL | Short-term value: 1050 mg/m ³ , 300 ppm Long-term value: 350 mg/m ³ , 100 ppm |
|-----|--|

1330-20-7 xylene

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

7440-50-8 copper

| | |
|-----|---|
| WEL | Short-term value: 2** mg/m ³ Long-term value: 0.2* 1** mg/m ³ *fume **dusts and mists (as Cu) |
|-----|---|

123-86-4 n-butyl acetate

| | |
|-----|---|
| WEL | Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm |
|-----|---|

· **Ingredients with biological limit values:**

1330-20-7 xylene

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

- **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: FAWORÌ CHROME EFFECT SPRAY PAINT COPPER

(Contd. of page 4)

· Protection of hands:


Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:


Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

| | |
|---------------------------|------------------------------------|
| Form: | Fluid |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |

· pH-value: Not determined.

· Change in condition

| | |
|---|---------------|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 81 °C |

· Flash point: -18 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 370 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

| | |
|---------------|-----------|
| Lower: | 1.1 Vol % |
| Upper: | 8.3 Vol % |

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: **FAWORI CHROME EFFECT SPRAY PAINT COPPER**

(Contd. of page 5)

| | |
|---|--|
| · Vapour pressure at 20 °C: | 104 hPa |
| · Density: | Not determined. |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with water: | Fully miscible. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 45.0 % |
| VOC (EC) | 45.00 % |
| Solids content: | 7.0 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

110-82-7 cyclohexane

| | | |
|------|------|--------------------|
| Oral | LD50 | 12,705 mg/kg (rat) |
|------|------|--------------------|

1330-20-7 xylene

| | | |
|------|------|-------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
|------|------|-------------------|

| | | |
|--------|------|----------------------|
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
|--------|------|----------------------|

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: FAWORÌ CHROME EFFECT SPRAY PAINT COPPER

(Contd. of page 6)

- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- | | |
|---|--|
| <ul style="list-style-type: none"> · 14.1 UN-Number · ADR, IMDG, IATA | <p>UN1263</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG · IATA | <p>1263 PAINT, ENVIRONMENTALLY HAZARDOUS, special provision 640D PAINT (CYCLOHEXANE, copper), MARINE POLLUTANT PAINT</p> |

(Contd. on page 8)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: **FAWORI CHROME EFFECT SPRAY PAINT COPPER**

(Contd. of page 7)

· 14.3 Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.
 · Label 3

· IMDG



· Class 3 Flammable liquids.
 · Label 3

· IATA



· Class 3 Flammable liquids.
 · Label 3

· 14.4 Packing group

· ADR, IMDG, IATA II

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances: cyclohexane

· Marine pollutant: Symbol (fish and tree)

· Special marking (ADR): Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Hazard identification number (Kemler code): 33

· EMS Number: F-E,S-E

· Stowage Category B

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category 2

· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: FAWORÌ CHROME EFFECT SPRAY PAINT COPPER

(Contd. of page 8)

| | |
|-----------------------------------|---|
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category**
E1 Hazardous to the Aquatic Environment
P5c FLAMMABLE LIQUIDS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t
- **National regulations:**
- **Information about limitation of use:**

| Class | Share in % |
|-------|------------|
| III | 7.0 |
| NK | 45.0 |

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Preparation date: 04.02.2021

Revision: 04.02.2021

Trade name: FAWORÌ CHROME EFFECT SPRAY PAINT COPPER

(Contd. of page 9)

*LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Gas 1: Flammable gases – Category 1**Press. Gas (Comp.): Gases under pressure – Compressed gas**Flam. Liq. 2: Flammable liquids – Category 2**Flam. Liq. 3: Flammable liquids – Category 3**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1**Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*

GB